



14<sup>th</sup> August 2012

Our Ref:

## DISPERSANT EFFICIENCY

### INTRODUCTION

The purpose of this work was to ascertain the efficiency of the dispersants, Slickgone NS, against the AMSA reference oil (Kuwait Crude topped) and an intermediate fuel oil (IFO180) and a heavy fuel oil (HFO 380).

The two fuel oils were sourced through AMOSC. The oils came in plastic bottles with the HFO having some literature on the bottle dated 7/1/2012 and a sheet with specifications for a FUELOIL\_380 dated 18/5/2012 (see attached photos). Presumably the spec data belongs to the same fuel oil supplied. Note that the viscosity and density on the bottle is greater than those on the spec sheet. No literature came with the IFO 180.

### TESTS

Fuel oils are difficult to use, particularly the heavy fuels, as they seem to solidify quickly once exposed to air and therefore it becomes difficult to measure the weight that is used in the MacKay tests. Good accuracy was displayed as the STD Dev between the two replicates was between 2 and 4 percent.

The MacKay apparatus was set to an air and seawater temperature of 20 °C with a moderate wave action height of 3.5 cm.

A 1:20 ratio is aimed at for the dispersant/oil mixture.

After a 10 minute period of mixing in the MacKay test chamber, a subsample is taken (A cut). The wind is then turned off. After a further 5 minutes, another subsample is taken (Q cut) and samples are subsequently extracted with Methylene Chloride.

### RESULTS

A good dispersant will immediately break up the oil to really fine droplets and will produce a coffee coloured appearance in the Mackay test chamber. The finer the droplets the longer they will stay in suspension and therefore the % recovery of oil in the "Q cut" (quiescence) ultimately determines this.

The dispersant was efficient in dispersing the AMSA reference oil and particularly with the IFO 180, where the % recovery was greater than 70.

In regards to the HFO 380, the oil took a few minutes before the dispersant started to break it up. Some of the oil would stay in clumps and some of it adhered to the test chamber as it started to solidify thus producing low recovery rates. Most of the oil did form droplets but were large enough to easily see and once the wave action was stopped they would find their way to the surface.

**Mackay Apparatus Settings**

Wave height	4 cm
Wind	7.9"
Temp water	20°C
Salinity	34

<b>IFO 180 + SLICKGONE NS</b>				
Test #	Weight of Oil	Wt of slickgone NS	%Oil recovered	
			10A	5Q
1	9.75	0.47	111.7	78.9
2	9.79	0.47	108.8	75.2
			<b>Mean</b>	110.3
			<b>Std Dev</b>	2.09
				77.1
				2.61

<b>HFO 380 + SLICKGONE NS</b>				
Test #	Weight of Oil	Wt of slickgone NS	%Oil recovered	
			10A	5Q
1	9.87	0.5	50.1	11.9
2	10.01	0.5	44.4	13.1
			<b>Mean</b>	47.3
			<b>Std Dev</b>	4.08
				12.5
				0.83

<b>AMSA REFERENCE OIL "KUWAIT CRUDE WEATHERED" + SLICKGONE NS</b>				
Test #	Weight of Oil	Wt of slickgone NS	%Oil recovered	
			10A	5Q
1	9.48	0.45	101.3	74.8
2	9.42	0.483	99.6	78.7
3	9.32	0.44	103.1	71.2
			<b>Mean</b>	101.3
			<b>Std Dev</b>	1.74
				74.9
				3.79