



SECTIONS OF UNIFORM SHIPPING LAWS TO APPLY UNDER NATIONAL SYSTEM

The sections below will be incorporated into NSCV Part C2 as marked when it is brought into effect.

Section 5, Sub-section C: Watertight sub-division of Passenger Vessels

Part I – Class 1 vessels 35 metres and over in measured length

C.42	Openings – Generally	(C2)
C.43	Side Scuttles not to be Capable of Being Opened	(C2)
C.44	Side Scuttle to be fitted with Watertight Deadlight	(C2)
C.45	Position of Side Scuttles	
C.46	Discharges and Inlets to Prevent Accidental Admission of Water	(C2)
C.47	Material for Cocks and Valves	(C2)
C.49	Discharge Pipes	(C2)
C.50	Bolts Connecting Fittings to Shell Plating	(C2)
C.51	Watertight Decks to be Drained	(C2)
C.52	Ash-chutes, Rubbish-chutes	(C2)
C.53	Ports	(C2)
C.54.2	(Openings Above the Bulkhead Deck)	(C2)
C.55	Bulkhead Deck to be Weathertight	(C2)
C.56	Openings in Weathertight Deck	(C2)
C.57	Deadlights	(C2)

Part II – Class 1 Vessels less than 35 metres in measured length

C.61.1	(Definitions) Cockpit	(C2)
C.61.2a	(Definitions) Designed load waterline	(C2)
C.61.3	(Definitions) Flush deck	(C2)
C.61.3a	(Definitions) Length	(C2)
C.61.4	(Definitions) Open vessel	(C2)
C.61.5	(Definitions) Well deck	(C2)
C.67	Drainage	(C2)
C.68	Hatches and Coamings	(C2)
C.69	Hull Penetrations and Shell Connections	(C2)
C.70	Ventilators in Class 1 Vessels Not Subject to the Load Lines Section	(C2)
C.71	Air Pipes in Class 1 Vessels Not Subject to the Load Lines Section	(C2)
C.72	Scuppers, Inlets and Discharges In Class 1 Vessels Not Subject to the Load Lines Section	(C2)

Part III – Provisions Applicable to all Class 1 Vessels

C.73	Wheelhouse and Deckhouse Windows	(C2)
------	----------------------------------	------

Section 5, Sub-section D: Watertight sub-division of Class 2 and Class 3 Vessels

Part I – Class 2 and Class 3 Vessels 35 metres and over in measured length

D.9	Openings – generally	(C2)
D.10	Side scuttles	(C2)
D.11	Discharges, inlets and scuppers	(C2)
D.12	Bolts connecting fittings to shell plating	(C2)
D.13	Watertight decks to be drained	(C2)
D.14	Rubbish-shoots	(C2)
D.15	Ports	(C2)

Part III – Special provisions applicable to Class 2 vessels not subject to the provisions of the Load Lines Section and Class 3 vessels other than such vessels to which Part IV applies

D.18	Watertight integrity	(C2)
D.19	Weathertight doors	(C2)
D.20	Hatchway coamings	(C2)
D.21	Hatchways closed by wood covers	(C2)
D.22	Hatchways closed by covers other than wood	(C2)
D.23	Machinery space openings	(C2)
D.24	Other deck openings	(C2)
D.25	Ventilators	(C2)
D.26	Air Pipes	(C2)
D.27	Side Scuttles and Skylights	(C2)
D.28	Scuppers, inlets and discharges	(C2)
D.29	Freeing ports	(C2)

Part IV – Modifications applicable to Class 2B and Class 2C vessels less than 16 metres in measured length, Class 3B and Class 3C vessels less than 20 meters in measured length, Class 2D, Class 2E, Class 3D, and Class 3E vessels

D.30	Openings in deckhouses or superstructures in which there are windows or side scuttles not fitted with hinged deadlights	(C2)
D.31	Hatchway coamings	(C2)
D.32	Hatchways on the weatherdeck closed by wood covers	(C2)
D.33	Hatchways on the weatherdeck closed by cover other than by wood	(C2)
D.34	Hatchways on a deckhouse top	(C2)

Part V – Provisions applicable to all Class 2 and Class 3 vessels

D.36	Wheelhouse and deckhouse windows	(C2)
------	----------------------------------	------

Section 7, Load Lines

All clauses	(C2)
-------------	------