

BIO REMEDIATES OIL AND FUEL SPILLS ON LAND & WATER

LITRES

S200 is a bioremediation accelerator that rapidly reduces hydrocarbons to water and carbon dioxide. S200 is effective on diesel, petrol, aviation fuel, kerosene, fuel oils #2 to #6, hydraulic oils, crude & lube oils. Ideal for both boat bilges, coastline and marina spills. Contains Butyl diglycol, urea, fatty acids, phosphate ester.

DIRECTIONS FOR USE

Apply S-200 Oil Gone in equal proportion to the oil spill On:

Water: Spray the entire oil sheen with S-200.

Land: Saturate by spraying the contaminated area. If the area is heavily contaminated, re-apply in 7 to 10 days.

Caution: Dilution significantly reduces product performance

IMPORTED BY

Gary Pearse Enterprises 2962 Tathra Bermagui Rd Murrah NSW 2546 Australia gpearse@ozemail.com.au Mobile +61 418 617 499

STORAGE

Keep container closed when not in use. Store away from foodstuffs, and between 5-38C°. Do not reuse container. Dispose of container in accordance with all applicable federal, state and local regulations. Shelf Life 18 months.

FIRST AID

Mild eye skin irritant. No medical conditions are known to be aggravated by exposure to this product. Under normal use the likelihood of adverse effects are very low.

EYES: Immediate flush with water, if irritation persists, see a doctor.

SKIN: Wash with water.

INGESTION: Drink water and see a doctor.

INHALATION: If breathing problems develops, move person to fresh air.

KEEP OUT OF REACH OF CHILDREN