

G-WASH[®]

MARINE CLEANER

HANDLING PRECAUTIONS

Keep out of reach of children. Slight eye irritant. Avoid contact with eyes. If eye contact occurs, immediately flush with water. If irritation persists, contact a physician. Use only as directed. Read and understand the label and SDS before using this product. Gecko Cleantech takes no responsibility for misuse or handling of the product.

APPLICATION

For surface cleaning dilute product between 1% and 10%. Small scale testing should be used to determine the optimum dilution rate prior to large-scale application. Apply diluted product directly to the contaminated surface through spraying or via saturated hydrophobic booms. For porous surfaces such as concrete, let dwell for 20-30 minutes, then remove oil using high-pressure spraying or manual agitation. Capture the oil using standard oil capture methods.

Dilution is not necessary for oil herding applications. Surround slick with sorbent booms prior to herding operation. Apply product to the centre of slick incrementally until all oil has been forced outwards. Oily booms may then be retrieved for disposal or recovery.



92 Lillkar Road, Goulburn NSW 2580
Phone: 1800 GECKOS (432 567)
e-mail: sales@gecko.com.au

www.gecko.com.au



GECKO CLEANTECH is a leading supplier of products for Spill Safety and Cleaning, such as sorbents, wiping cloths, bunding, and dangerous goods storage equipment.

Contact us to learn how you can reduce your costs and environmental impact!